





- Processes up to 15,500 sheets per hour
- Color touchscreen control panel
- Fold plates marked with 6 popular folds
- Telescoping output conveyor
- Infeed holds up to 500 sheets



www.formax.com

Local Dealer:

The FD 346 Document Folder is a fast, dependable, easy-to-use solution for virtually all folding applications. The color touchscreen control panel uses internationally-recognized symbols in place of text, making it easy for anyone to use. Six popular folds are clearly marked on the fold plates. Simply load the feeder with up to 500 sheets, and after folding, the FD 346 will hold the finished pieces on patented telescoping conveyor system. Additional features include AutoBatch for processing sets of documents, adjustable output stacker wheels, a cross-folding guide for two-pass operation, and the ability to set custom folds. The optional multi-sheet feeder allows up to 4 stapled or unstapled sheets to be folded at one time.



Color Touchscreen Control Panel Utilizes easily-recognized symbols in place of text




Adjustable Stacker Wheels Neatly stack different paper sizes and fold types



**Optional Multi-Sheet Feeder** Up to 4 stapled or unstapled sheets can be folded at once



Telescoping Conveyor System Extends from 14" to 36" in length and holds up to 500 folded pieces



Pre-Marked for Standard Folds Fold plates are clearly marked for six popular fold types

STANDARD FEATURES	OPTIONS	SPECIFICATIONS			
Folds up to 15,500 pieces per hour	Multi-sheet feeder	Speed	Up to 15,500 sheets per hour, based on 11" Z-Fold		
Color touchscreen	Locking cabinet				
Drop-in three-roller feed system		Hopper Capacity	Up to 500 sheets 20#		
Adjustable stacker wheels	stable stacker wheels		C, V, Z, Gate, Fold Out,		
Telescoping conveyor holds up to 500 sheets			and Double Parallel		
6-Digit resettable & 8-Digit life counters AutoBatch <b>™ programmable setting</b>		Paper Sizes	Min: 3.5" W x 5" L (89 x 127mm) Max: 12.25" W x 18" L (311 x 457mm)		
				Pre-marked for six folds in common paper sizes	3
Custom folds			60" L x 20" W x 19" H (1524 x 508 x 483mm)		
Quick release fold stops		Weight	67 lbs (30kg)		
Fine-tune adjustment Cross-folding guide for two-pass operation Easy-off feed wheel shaft Self centering side guides		Power	FD Model: 110VAC 50/60 Hz FE Model: 220VAC 50/60 HZ		
				Safety Certifications	UL, CUL, and CE approved
		Fault detection			

6/2024