

FD 430 Envelope Sealer

ONE-PASS MAIL PROCESSING





- Seals up to 18,000 envelopes per hour
- Processes envelopes up to 16mm thick
- Variable speed control knob
- Flap closing bar for nested open envelopes
- Large outfeed tray



Local Dealer:

The FD 430 Envelope Sealer closes and seals envelopes in a single pass. Users can process envelopes up to 9.75" wide x 15" long, up to 16 mm thick, at speeds of up to 18,000 per hour. Standard features include a variable speed control, adjustable envelope separator to ensure accurate feeding, a large outfeed tray, heavy-duty metal construction and a precision moistening roller. The flap closing bar allows users to load envelopes in a standard stack or nested with flaps open for even greater efficiency. Forget the days of hand-sealing envelopes, and let the FD 430 seal your mail in the blink of an eye.



Variable Speed Control Knob Envelopes can be processed at speeds of up to 18,000 per hour



Precision Moistening Roller Rubber roller is designed to efficiently transfer water to the flap



Adjustable Outfeed Tray
Outfeed tray accommodates a wide
variety of envelope sizes



Flap Closing Bar Allows for loading envelopes nested with flaps open



Adjustable Envelope Separator
Ensures envelopes are fed one at a time
for accurate sealing

STANDARD FEATURES

Simply load, choose speed, and go

Processes up to 18,000 pieces an hour

Handles envelopes up to 16mm thick

Variable speed control

Seals envelopes up to 9.75" W, 15" long

Precision moistening roller

Flap closing bar for nested open envelopes

Adjustable separator ensures single feeding

Large outfeed tray

Heavy-duty steel construction

OPTIONS

FD 430-10 Extended Sealing Kit for flaps up to 4" long

FD 430-20 Square Flap Moistening Basin and Roller

SPECIFICATIONS

Speed Up to 18,000 envelopes per hour

Infeed Capacity Up to 4.5" stack height* (114mm)

Outfeed Capacity Up to 4.5" stack height* (114mm)

Media Size Up to 9.75" W (248mm)

Up to 15" L (381mm)

Envelope Flap Length Standard: up to 2.75" (70mm)

Extended: up to 4" (102mm) (w/optional extended sealing kit)

Package Thickness Up to 16mm

 $\begin{array}{ll} \hbox{Dimensions} & 43\text{"L}\,\text{x}\,15\text{"H}\,\text{x}\,15\text{"D} \\ \hbox{(including outfeed tray)} & (109\,\text{x}\,381\,\text{x}\,381\text{cm}) \end{array}$

Weight 55 lbs (25kg)

Power 110V, 60Hz

Safety Certification CE

*Variable, depending on thickness of envelope & contents