



ReadyWire Electric

ELECTRIC PUNCHING & BINDING • 2E (2:1) OR 3E (3:1 PITCH)



PREMIUM OFFICE WIRE PUNCH & BINDING SYSTEMS



**All-in-One
Ergonomic Workflow**



Foot pedal activates punch

- Heavy-duty compact binding system
- Two models available: 2E (2:1 pitch) or 3E (3:1 pitch)
- Ergonomic workflow from punching to binding
- Simple, electric foot pedal operation
- Precision vertical punching

FORMAX®

www.formax.com

Local Dealer:

The **ReadyWire2E (2:1 Pitch)** and **3E (3:1 Pitch) Electric Punching & Binding Systems** deliver the speed and convenience of electric punching. With rugged **all-metal construction**, and **simple foot pedal activation**, they're built to last, and designed for easy use. The **precision vertical punching system** utilizes gravity to keep every sheet in place, for consistent hole placement even on larger document sets. **Setup is quick and easy with no tools required.** Each pitch style (2:1 and 3:1) produces professionally bound booklets, with the **2:1 Pitch having an advantage in its versatility** to accommodate a wide range of wire bindings from 1/4" to 1 1/2" in diameter, for booklets up to 340 sheets. Wire-bound documents open a full 360 degrees, laying flat for easier reading, writing, scanning, and presentations, and the **double-loop wire binding** keeps pages secure for a polished appearance through years of use.




Easy Access to Punch Pins

Disengage selected pins to prevent partially punched holes.
No tools required.




Precision Vertical Punching

Utilizes gravity for consistent hole placement.




Formax ReadyWire Binding

Packaged in patented wire sheets to keep them organized, undamaged and easy to remove.



ReadyWire2E - 2:1 Pitch

Formax Recommended - Greater versatility, wire diameters 1/4" to 1 1/4", up to 280 sheets.



ReadyWire3E - 3:1 Pitch

More refined look, limited wire diameters 1/4" to 5/8", up to 135 sheets.

STANDARD FEATURES

- Heavy-duty compact design
- Convenient electric foot pedal operation
- Quick, easy adjustments
- Closure control adjustment
- Precision vertical punching system
- Individually disengageable punch pins
- Smooth, quiet operation
- Depth gauge for stronger bind
- Specially hardened punch pins
- Parallel adjustment for accuracy
- Integrated wire comb holding device
- Easy-empty sliding waste tray

SUPPLIES - ReadyWire Double-Loop

- Packaged in patented wire sheets to keep them neatly organized, undamaged, and easy to remove
- Available in diameters from 1/4" to 1 1/2"
- Thicker than industry standard
- Designed to close in a perfect circle

SPECIFICATIONS

	ReadyWire2E	ReadyWire3E
Punching Capacity	Up to 16,000 sheets/hr	Up to 16,000 sheets/hr
Pitch	2:1	3:1
Punching/Binding	Electric/Manual	Electric/Manual
Punching Width	.39" (10mm) - 14" (360mm)	.39" (10mm) - 14" (360mm)
Max. Punching Thickness	Up to 0.10" (2.5mm)	Up to 0.08" (2.2mm)
Punch Hole Dimensions	Rectangle 5.5 x 3.5mm	Square 4 x 4mm
Binding Speed	Up to 250 books/hr	Up to 250 books/hr
Binding Capacity	Up to 340 sheets	Up to 135 sheets
Wire Diameter	1/4" to 1 1/2"	1/4" to 5/8"
Disengageable Punch Pins	Yes	Yes
Variable Margin Depth	Yes	Yes
Dimensions	22" W x 16" D x 10.75" H (560 x 406 x 273mm)	22" W x 16" D x 10.75" H (560 x 406 x 273mm)
Power	115/200V, 60HZ, 180W	115/200V, 60HZ, 180W
Weight	28.6 lbs. (13kg)	28.6 lbs. (13kg)